



HTX & SXHT Series Hydronic Expansion Tanks

QUICK SIZING GUIDE				
Boiler Output 1000's BTUH	Copper Baseboard & Radiant	Type of Radiation		
		Convectors & Unit Heaters	Cast Iron	
			Radiators	Baseboard
25	HTX 15	HTX 15	HTX 15	HTX 15
50	HTX 15	HTX 30	HTX 30	HTX 30
75	HTX 30	HTX 30	HTX 60	HTX 60
100	HTX 30	HTX 30	HTX 60	HTX 60
125	HTX 30	HTX 60	HTX 60	HTX 60
150	HTX 30	HTX 60	HTX 90	HTX 90
175	HTX 60	HTX 60	HTX 90	HTX 90
200	HTX 60	HTX 60	HTX 90	HTX 90
250	SXHT 30	SXHT 30	SXHT 40	SXHT 30
300	SXHT 30	SXHT 40	SXHT 40	SXHT 30
350	SXHT 30	SXHT 40	SXHT 60	SXHT 40
400	SXHT 30	SXHT 60	SXHT 90	SXHT 40
500	SXHT 40	SXHT 60	SXHT 90	SXHT 40
600	SXHT 40	SXHT 90	SXHT 90	SXHT 60
700	SXHT 60	SXHT 90	SXHT 90	SXHT 60
800	SXHT 60	SXHT 110	SXHT 110	SXHT 90
900	SXHT 60	SXHT 110	SXHT 110	SXHT 90
1000	SXHT 90	SXHT 110	SXHT 110	SXHT 90

Sizing recommendations based on average size systems.
 Fill pressure 12 PSI. Relief valve 30 PSI.
 Average system water temperature 200°F.

300 Pond Street, Randolph, Massachusetts 02368
 Call 1.781.986.2424 • Fax 1.781.986.2029
www.flexconind.com



HTX & SXHT Series Hydronic Expansion Tanks

COMPETITIVE CROSS-REFERENCE GUIDE						
FLEXCON	VENT-RITE	AMTROL	WATTS	STATE	ELBI	WILKINS
HTX 15	VR15	15	ET-15	ET-20	XT-15	HXT-15
HTX 30	VR30	30	ET-30	ET-5	XT-30	HXT-30
HTX 60	VR60	60	ET-60	ET-7	XT-60	HXT-60
HTX 90	VR90	90	ET-90	ET-14	XT-90	HXT-90
SXHT 30	SXVR30	SX30	N/A	ET-15	XTV-30	N/A
SXHT 40	SXVR40	SX40	N/A	ET-20	XTV-40	N/A
SXHT 60	SXVR60	SX60	N/A	ET-36	XTV-60	N/A
SXHT 90	SXVR90	SX90	N/A	ET-52	XTV-90	N/A
SXHT 110	SXVR110	SX110	N/A	N/A	XTV-110	N/A
SXHT 160	SXVR160	SX160	N/A	ET-96	XTV-160	N/A